Externally Threaded Ring - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5365-00-111-7333



## Thread Pitch Diameters:

+2.6116 to 2.6157 inches

## **Thread Direction:**

**Right-hand** 

#### **Casehardening Indicator:**

Not casehardened

#### Width:

Between 0.250 inches and 0.270 inches

#### **Overall Length:**

0.520 inches

**Thread Size:** 

2.6563 in. -16

#### Bore Diameter:

Between 2.390 inches and 2.410 inches

#### Depth:

Between 0.120 inches and 0.140 inches

#### Bore Shape:

Straight

## Screw Thread Series Designator:

Nonstandard

#### Drive Type:

Slotted face

#### Material Hardness Rating:

Between 30.0 rockwell c and 38.0 rockwell c

#### **Thread Location:**

Both ends

#### Accommodation Type And Quantity:

12 slots

#### Angle Between Accommodations In Deg:

30.0

### **Beveled Thread:**

Included

## Bore Annular Internal Serration:

Not included

## Setscrew Locking Notch:

Not included

## Material:

Steel, ams 5616

Material:

Steel comp 615

## **Fsc Application Data:**

Fuel filter, engine, aircraft ndup of fsn 2840-703-9225

# NSN 5365-00-111-7333

Externally Threaded Ring - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

T252-d