## NSN 5365-00-133-9778

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-133-9778 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.060 inches **Overall Length:** Between 0.920 inches and 0.940 inches Diameter: Between 0.328 inches and 0.333 inches **Thread Size:** 6.750-12 **Bore Diameter: 5.380** inches Depth: 0.440 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns **Drive Type:** Drilled face **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 3.000 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** 

Not included **Bore Edge Process:**Chamfered

## NSN 5365-00-133-9778

Externally Threaded Ring - Page 2 of 2



<b>Process</b>	End	Location:
		-oution.

Both ends

Material:

Steel, qq-s-624, comp 4130-canceled or steel, qq-s-624, comp 8630-canceled or steel, qq-s-626, comp 4130 or steel, qq-s-626, comp 8630

## **Surface Treatment:**

Cadmium and phosphate

**Surface Treatment:** 

Cadmium plated finish, qq-p-416a, type 2, class 3

Shelf Life:

N/a

**Unit Of Measure:** 

--

## Demilitarization:

Yes - demil/mli

Fiig:

T252-d