NSN 5365-00-135-7028

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-135-7028 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Chamfer Angle In Deg: 45.0 **Chamfer Length:** 0.070 inches Width: Between 0.245 inches and 0.255 inches **Overall Length:** Between 0.760 inches and 0.780 inches **Thread Size:** 2.500 in-16 thd size **Bore Diameter:** Between 2.115 inches and 2.125 inches Depth: 0.260 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unf **Drive Type:** Slotted face **Material Hardness Rating:** C30 to c38 **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:**

Not included **Bore Edge Process:** Chamfered **Process End Location:** End opposite drive end

NSN 5365-00-135-7028

Externally Threaded Ring - Page 2 of 2



NЛ	ate	ria	
IVI	ale	110	ı .

Steel, ams 5613, comp 30304

Surface Treatment:

Silver

Surface Treatment:

Silver plated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T252-d