## NSN 5365-00-136-4927

Externally Threaded Ring - Page 1 of 2



, , , , , , , , , , , , , , , , , , , ,
View Online at https://aerobasegroup.com/nsn/5365-00-136-4927
Thread Pitch Diameters:
+0.8668 to 0.9051 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Overall Length:
0.672 inches
Diameter:
0.093 inches
Thread Size:
0.906-32
Bore Diameter:
0.860 inches
Depth:
0.060 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Drilled face
Accommodation Type And Quantity:
2 holes
Angle Between Accommodations In Deg:
180.0
Radius From Geometric Axis To Accommodation:
0.453 inches
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:

Not included

Material:

Steel, qq-s-763, class 303, cond a

Material:

Steel comp 303

**Surface Treatment:** 

Passivate

**Surface Treatment:** 

Passivated, mil-std-171, finish 5.4.1

## NSN 5365-00-136-4927

Externally Threaded Ring - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d