Externally Threaded Ring - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5365-00-136-8130

| Thread Class: | |
|--------------------------------------|--|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Casehardening Indicator: | |
| Not casehardened | |
| Width: | |
| 0.375 inches | |
| Overall Length: | |
| 1.380 inches | |
| Thread Size: | |
| 5-3/4 in12 thd size | |
| Bore Diameter: | |
| 5.007 inches | |
| Depth: | |
| 0.156 inches | |
| Bore Shape: | |
| Straight | |
| Screw Thread Series Designator: | |
| Un | |
| Drive Type: | |
| Slotted face | |
| Material Hardness Rating: | |
| Not rated | |
| Thread Location: | |
| Both ends | |
| Accommodation Type And Quantity: | |
| 4 slots | |
| Angle Between Accommodations In Deg: | |
| 90.0 | |
| Beveled Thread: | |
| Included | |
| Bore Annular Internal Serration: | |
| Not included | |
| Setscrew Locking Notch: | |
| Included | |
| Material: | |
| Copper alloy, qq-c-390, alloy 954 | |
| Material: | |
| Copper alloy 954 | |
| Surface Treatment: | |
| Cadmium | |
| | |

NSN 5365-00-136-8130

Externally Threaded Ring - Page 2 of 2

Surface Treatment:

Cadmium plated

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d

