## NSN 5365-00-141-6214



Externally Threaded Ring - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-00-141-6214 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.025 inches Width: 0.250 inches **Overall Length:** 0.190 inches **Thread Size:** 5-13/16 in.-32 **Bore Diameter: 5.380** inches Depth: Between 0.051 inches and 0.061 inches Bore Shape: Straight **Screw Thread Series Designator:** Nonstandard **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** Both ends

Material: Aluminum alloy, mil-t-5063, type 3

## NSN 5365-00-141-6214

Externally Threaded Ring - Page 2 of 2



Material:
-----------

Aluminum alloy, mil-t-5063, type 3

**Surface Treatment:** 

Anodize

**Surface Treatment:** 

Anodized black

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d