Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-152-6215

Rig <b>Ca</b> Not <b>Wid</b> 0.0 <b>Ov</b> 0.2	read Direction: ht-hand sehardening Indicator: a casehardened dth: 62 inches erall Length: 81 inches read Size:
Rig <b>Ca</b> Not <b>Wid</b> 0.0 <b>Ov</b> 0.2	ht-hand sehardening Indicator: casehardened dth: 62 inches erall Length: 81 inches
Ca: Not 0.0 0.0 0.2	sehardening Indicator: casehardened dth: 62 inches erall Length: 81 inches
Noi Wi 0.0 <b>Ov</b> 0.2	a casehardened dth: 62 inches erall Length: 81 inches
<b>Wi</b> 0.0 <b>Ov</b> 0.2	dth: 62 inches erall Length: 81 inches
0.0 <b>Ov</b> 0.2	62 inches erall Length: 81 inches
<b>Ov</b> 0.2	erall Length: 81 inches
0.2	81 inches
Th	read Size:
1.5	00-32
Во	re Diameter:
1.1	56 inches
De	oth:
0.0	62 inches
Во	re Shape:
Stra	aight
Sci	rew Thread Series Designator:
Un	əf
Dri	ve Туре:
Slo	tted face
Ac	commodation Type And Quantity:
2 s	lots
An	gle Between Accommodations In Deg:
180	).0
Be	veled Thread:
Not	included
Во	re Annular Internal Serration:
Not	included
Set	screw Locking Notch:
Not	included
Sp	ecial Features:
Ce	nter hole counter-sunk 15 degrees angle to 1.250 in. Diameter at drive end
Ma	terial:
Alu	minum alloy, mil-a-268, t4
Sh	elf Life:
N/a	
Un	it Of Measure:
De	militarization:

## NSN 5365-00-152-6215

Externally Threaded Ring - Page 2 of 2

**Fiig:** T252-d

