Externally Threaded Ring - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5365-00-157-3884                   |  |
|---|--|
| Thread Class:   |  |
| 3a  |  |
| Thread Direction:   |  |
| Right-hand  |  |
| Casehardening Indicator:  |  |
| Not casehardened  |  |
| Width:  |  |
| 0.080 inches  |  |
| Overall Length:   |  |
| 0.280 inches  |  |
| Thread Size:  |  |
| 2-1/16 in32   |  |
| Bore Diameter:  |  |
| 1.850 inches  |  |
| Depth:  |  |
| 0.040 inches  |  |
| Bore Shape:   |  |
| Straight  |  |
| Screw Thread Series Designator:   |  |
| Uns   |  |
| Drive Type:   |  |
| Slotted face  |  |
| Thread Location:  |  |
| End opposite drive end  |  |
| Accommodation Type And Quantity:  |  |
| 2 slots   |  |
| Angle Between Accommodations In Deg:  |  |
| 180.0   |  |
| Beveled Thread:   |  |
| Included  |  |
| Bore Annular Internal Serration:  |  |
| Not included  |  |
| Setscrew Locking Notch:   |  |
| Included  |  |
| Special Features:   |  |
| Center hole counterbored 0.260 in. Porm .005 deep from opposite of slotted face |  |
| Material:   |  |
| Brass, mil-b-994, comp b, 1/2 hard-canceled                                     |  |
| Material:   |  |
| Copper alloy 482  |  |
| Shelf Life:   |  |
| N/a   |  |
|   |  |

## NSN 5365-00-157-3884

Externally Threaded Ring - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

T252-d