

View Online at <https://aerobasegroup.com/nsn/5365-00-168-6591>

**Thread Pitch Diameters:**

+0.8811 to 0.8849 inches

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Overall Length:**

Between 0.360 inches and 0.370 inches

**Diameter:**

0.093 inches

**Thread Size:**

0.906-32

**Bore Diameter:**

Between 0.270 inches and 0.280 inches

**Depth:**

0.047 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Drilled face

**Accommodation Type And Quantity:**

2 holes

**Angle Between Accommodations In Deg:**

180.0

**Radius From Geometric Axis To Accommodation:**

0.344 inches

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Material:**

Steel, qq-s-763, class 304 cond a or steel, astm a-582, type 303 cond a or steel, astm a-582, type 303se cond a

**Material:**

Steel, qq-s-763, class 304 cond a or steel, astm a-582, type 303 cond a or steel, astm a-582, type 303se cond a

**Surface Treatment:**

Passivate

**Surface Treatment:**

Passivated, mil-std-171, finish 5.4.1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d