

View Online at <https://aerobasegroup.com/nsn/5365-00-168-6591>

Thread Pitch Diameters:

+0.8811 to 0.8849 inches

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Overall Length:

Between 0.360 inches and 0.370 inches

Diameter:

0.093 inches

Thread Size:

0.906-32

Bore Diameter:

Between 0.270 inches and 0.280 inches

Depth:

0.047 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Uns

Drive Type:

Drilled face

Accommodation Type And Quantity:

2 holes

Angle Between Accommodations In Deg:

180.0

Radius From Geometric Axis To Accommodation:

0.344 inches

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Material:

Steel, qq-s-763, class 304 cond a or steel, astm a-582, type 303 cond a or steel, astm a-582, type 303se cond a

Material:

Steel, qq-s-763, class 304 cond a or steel, astm a-582, type 303 cond a or steel, astm a-582, type 303se cond a

Surface Treatment:

Passivate

Surface Treatment:

Passivated, mil-std-171, finish 5.4.1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d