## NSN 5365-00-168-6932

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-168-6932
Thread Pitch Diameters:
+1.4773 to 1.4808 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Overall Length:
0.095 inches
Diameter:
Between 0.065 inches and 0.075 inches
Thread Size:
1.500-36
Bore Diameter:
Between 1.215 inches and 1.310 inches
Depth:
0.050 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Drilled face
Thread Location:
Both ends
Accommodation Type And Quantity:
2 holes
Angle Between Accommodations In Deg:
180.0
Radius From Geometric Axis To Accommodation:
0.675 inches
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Satesray Looking Notes

**Setscrew Locking Notch:** 

Not included

Material:

Steel, astm a-582, type 303, cond a

Material:

Steel, astm a-582, type 303, cond a

**Surface Treatment:** 

Passivated 990104 type 1 fscm 00481

## NSN 5365-00-168-6932

Externally Threaded Ring - Page 2 of 2



	Trea	

Passivated 990104 type 1 fscm 00481

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d