## NSN 5365-00-173-0480

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-173-0480 **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.015 inches Width: Between 0.032 inches and 0.037 inches **Overall Length:** 0.094 inches **Thread Size:** 0.991-48 **Bore Diameter:** 0.844 inches Depth: 0.031 inches Bore Shape: Straight **Screw Thread Series Designator:** Nonstandard **Drive Type:** Slotted face **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** Both ends Material: Aluminum alloy, qq-a-250/5, t3 Material: Aluminum alloy 2024 and aluminum alloy 1230

## NSN 5365-00-173-0480

Externally Threaded Ring - Page 2 of 2



Surface	Treatment:
Anodize	

**Surface Treatment:** 

Anodized, mil-a-8625, type 1, class 2

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d