

View Online at <https://aerobasegroup.com/nsn/5365-00-174-3731>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.040 inches

**Overall Length:**

0.593 inches

**Diameter:**

Between 0.155 inches and 0.161 inches

**Thread Size:**

1.250-12

**Bore Diameter:**

Between 0.625 inches and 0.626 inches

**Depth:**

0.100 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unf

**Drive Type:**

Drilled face

**Accommodation Type And Quantity:**

4 holes

**Angle Between Accommodations In Deg:**

90.0

**Radius From Geometric Axis To Accommodation:**

0.453 inches

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

End opposite drive end

**Special Features:**

One locking element nas 1283 type n on periphery of thd, internal groove 0.801 in. Diameter by 0.188 in. Wide at 0.220 in. From drive end

**Material:**

Steel, corrosion resisting

**Material:**

Stainless steel

**Surface Treatment:**

Passivate hp4-169 82577

**Surface Treatment:**

Passivate hp4-169 82577

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d