Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-174-3731

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Casehardening Indicator:	
Not casehardened	
Chamfer Angle In Deg:	
45.0	
Chamfer Length:	
0.040 inches	
Overall Length:	
0.593 inches	
Diameter:	
Between 0.155 inches and 0.161 inches	
Thread Size:	
1.250-12	
Bore Diameter:	
Between 0.625 inches and 0.626 inches	
Depth:	
0.100 inches	
Bore Shape:	
Straight	
Screw Thread Series Designator:	
Unf	
Drive Type:	
Drilled face	
Accommodation Type And Quantity:	
4 holes	
Angle Between Accommodations In Deg:	
90.0	
Radius From Geometric Axis To Accommodation:	
0.453 inches	
Beveled Thread:	
Not included	
Bore Annular Internal Serration:	
Not included	
Setscrew Locking Notch:	
Not included	
Bore Edge Process:	
Chamfered	
Process End Location:	
End opposite drive end	

NSN 5365-00-174-3731

Externally Threaded Ring - Page 2 of 2



Special Features:

One locking element nas 1283 type n on periphery of thd, internal groove 0.801 in. Diameter by 0.188 in. Wide at 0.220 in. From drive end

Material:

Steel, corrosion resisting

Material:

Stainless steel

Surface Treatment:

Passivate hp4-169 82577

Surface Treatment:

Passivate hp4-169 82577

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d