Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-176-5434

Thread Class: Ba Thread Direction: Right-hand Casehardening Indicator: Not casehardened Chamfer Angle In Deg: 15.0 Chamfer Length: 10.022 inches Diverall Length: 10.171 inches Diameter: 10.070 inches Thread Size: 1.359 in .40 Bore Diameter: 121 inches Depth:
Thread Direction: Right-hand Casehardening Indicator: Not casehardened Chamfer Angle In Deg: 15.0 Chamfer Length: 0.022 inches Overall Length: 0.171 inches Diameter: 0.070 inches Thread Size: .359 in40 Bore Diameter: .121 inches Depth:
Right-hand Casehardening Indicator: Not casehardened Chamfer Angle In Deg: 15.0 Chamfer Length: 0.022 inches Doverall Length: 0.022 inches Diameter: 0.070 inches Thread Size: .359 in40 Bore Diameter: .121 inches Depth:
Casehardening Indicator: Not casehardened Chamfer Angle In Deg: 15.0 Chamfer Length: 0.022 inches Overall Length: 0.171 inches Diameter: 0.070 inches Thread Size: .359 in40 Bore Diameter: .121 inches
Not casehardened Chamfer Angle In Deg: 15.0 Chamfer Length: 0.022 inches Dverall Length: 0.171 inches Diameter: 0.070 inches Thread Size: .359 in40 Bore Diameter: .121 inches
 b. 2. Chamfer Length: b. 0.022 inches b. 0.022 inches b. 0.021 inches b. 0.070 inches b. 0.070 inches c. 0.070 inches <lic. 0.070="" inches<="" li=""> <lic. 0.070="" inches<="" li=""> <lic. 0.070<="" td=""></lic.></lic.></lic.>
 b. 2. Chamfer Length: b. 0.022 inches b. 0.022 inches b. 0.021 inches b. 0.070 inches b. 0.070 inches c. 0.070 inches <lic. 0.070="" inches<="" li=""> <lic. 0.070="" inches<="" li=""> <lic. 0.070<="" td=""></lic.></lic.></lic.>
0.022 inches Dverall Length: 0.171 inches Diameter: 0.070 inches Thread Size: 1.359 in40 Bore Diameter: 1.121 inches Depth:
0.022 inches Dverall Length: 0.171 inches Diameter: 0.070 inches Thread Size: 1.359 in40 Bore Diameter: 1.121 inches Depth:
0.171 inches Diameter: 0.070 inches Thread Size: 0.359 in40 Bore Diameter: 0.121 inches Depth:
Diameter: 0.070 inches Thread Size: .359 in40 Bore Diameter: .121 inches Depth:
0.070 inches Thread Size: .359 in40 Bore Diameter: .121 inches Depth:
Thread Size: .359 in40 Bore Diameter: .121 inches Depth:
.359 in40 Bore Diameter: .121 inches Depth:
Bore Diameter: .121 inches Depth:
.121 inches Depth:
Depth:
0.171 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Jns
Drive Type:
Drilled face
Accommodation Type And Quantity:
2 holes
Angle Between Accommodations In Deg:
80.0
Radius From Geometric Axis To Accommodation:
Between 0.610 inches and 0.613 inches
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
Chamfered
Process End Location:
Both ends

NSN 5365-00-176-5434

Externally Threaded Ring - Page 2 of 2



Material:

Brass, ww-t-791, grade 2, type a

Material:

Copper alloy 330

Fsc Application Data:

Indicator, course automatic pilot, aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d