NSN 5365-00-177-3931

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-177-3931 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 30.0 **Chamfer Length:** 0.002 inches Width: 0.040 inches **Overall Length:** 0.220 inches **Thread Size:** 1.062 in.-32 **Bore Diameter:** 0.980 inches Depth: 0.040 inches Bore Shape: Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:**

Drive end

NSN 5365-00-177-3931Externally Threaded Ring - Page 2 of 2



| Material: | |
|--------------------------------|---|
| Aluminum alloy, ww-t-700/3, to | 3 |
| Material: | |
| Aluminum alloy 2024 | |
| Surface Treatment: | |
| Oxide | |
| Surface Treatment: | |
| Black oxide | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

Fiig: T252-d