Externally Threaded Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-00-183-6330

| Thread Class: | |
|---|--|
| 3a | |
| Sa Thread Direction: | |
| Right-hand | |
| Casehardening Indicator: | |
| Not casehardened | |
| Width: | |
| 0.190 inches | |
| Overall Length: | |
| Between 0.540 inches and 0.550 inches | |
| Thread Size: | |
| 2.875-16 | |
| Depth: | |
| Between 0.180 inches and 0.190 inches | |
| Screw Thread Series Designator: | |
| Un | |
| Drive Type: | |
| Slotted face | |
| Accommodation Type And Quantity: | |
| 6 slots | |
| Angle Between Accommodations In Deg: | |
| 60.0 | |
| Beveled Thread: | |
| Not included | |
| Bore Annular Internal Serration: | |
| Not included | |
| Setscrew Locking Notch: | |
| Not included | |
| Material: | |
| Steel, mil-t-6736, cond ht-150 | |
| Surface Treatment: | |
| Cadmium plated, stf0175 type 2, class 3 76823 | |
| Surface Treatment: | |
| Cadmium plated, stf0175 type 2, class 3 76823 | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| T252-d | |