NSN 5365-00-200-5389



Externally Threaded Ring - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-00-200-5389 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.250 inches Diameter: 0.104 inches **Thread Size:** 2-3/4 in.-32 **Bore Diameter:** 2.310 inches Depth: 0.125 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns or ns **Drive Type:** Drilled face **Accommodation Type And Quantity:** 2 holes Angle Between Accommodations In Deg: 180.0 **Radius From Geometric Axis To Accommodation:** 2.500 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** End opposite to drive end counterbored to 2.50 in. Plus 0.010 in. Diameter by 0.03 in. Plus 0.010 in. Deep and periphery of end opposite to drive end machined to 2.610 in. Minus 0.010 in. Diameter by 0.030 in. Plus 0.010 in. Deep

Material:

Steel, qq-s-637, comp b1112

Material:

Steel comp 1212

Surface Treatment:

Oxide

NSN 5365-00-200-5389

Externally Threaded Ring - Page 2 of 2



$\overline{}$			-			
~ I	ırfa	ഫ	ırc	natr	nΔn	

Black oxide

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d