Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-200-5470

| Thread Class: |
|--------------------------------------|
| 2a |
| Thread Direction: |
| Right-hand |
| Casehardening Indicator: |
| Not casehardened |
| Width: |
| 0.047 inches |
| Overall Length: |
| 0.156 inches |
| End Radius: |
| 0.010 inches |
| Thread Size: |
| 1-5/16 in32 |
| Bore Diameter: |
| 1.174 inches |
| Depth: |
| 0.047 inches |
| Bore Shape: |
| Straight |
| Screw Thread Series Designator: |
| Ns or uns |
| Drive Type: |
| Slotted face |
| Material Hardness Rating: |
| Not rated |
| Accommodation Type And Quantity: |
| 2 slots |
| Angle Between Accommodations In Deg: |
| 180.0 |
| Beveled Thread: |
| Not included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Bore Edge Process: |
| Rounded |
| Process End Location: |
| End opposite drive end |
| Special Features: |
| |

Periphery of end opposite to drive end machined to 1.250 in. Porm 0.010 diameter by 0.050 in. Porm 0.010 lg

NSN 5365-00-200-5470

Externally Threaded Ring - Page 2 of 2

Material:

Aluminum alloy, ww-t-785-canceled

Material:

Aluminum alloy 2024

Surface Treatment:

Black dye

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d

