## NSN 5365-00-200-5471

Externally Threaded Ring - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5365-00-200-5471 |
|---|
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Casehardening Indicator:                                      |
| Not casehardened  |
| Width:  |
| 0.063 inches  |
| Overall Length:   |
| 0.188 inches  |
| Thread Size:  |
| 1-13/16 in32  |
| Bore Diameter:  |
| 1.650 inches  |
| Depth:  |
| 0.031 inches  |
| Bore Shape:   |
| Straight  |
| Screw Thread Series Designator:                               |
| Uns   |
| Drive Type:   |
| Slotted face  |
| Accommodation Type And Quantity:                              |
| 2 slots   |
| Angle Between Accommodations In Deg:                          |
| 180.0   |
| Beveled Thread:   |
| Not included  |
| Bore Annular Internal Serration:                              |
| Not included  |
| Setscrew Locking Notch:                                       |
| Included  |
| Material:   |
| Aluminum alloy, ww-t-785-canceled                             |
| Material:   |
| Aluminum alloy 2024   |
| Surface Treatment:  |
| Black dye   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5365-00-200-5471

Externally Threaded Ring - Page 2 of 2



Demilitarization:

No

Fiig:

T252-d