## NSN 5365-00-200-5479

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-200-5479 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.063 inches **Overall Length:** 0.250 inches **End Radius:** 0.010 inches **Thread Size:** 1-13/16 in.-32 **Bore Diameter:** 1.612 inches Depth: 0.063 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns or ns **Drive Type:** Slotted face **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Any acceptable **Process End Location:** End opposite drive end **Special Features:** 

Periphery of drive end machined to 1.75 in. Porm 0.010 diameter by 0.080 in. Porm 0.010 lg

## NSN 5365-00-200-5479

Externally Threaded Ring - Page 2 of 2



	eria	

Aluminum alloy, ww-t-785-canceled

Material:

Aluminum alloy 2024

**Surface Treatment:** 

Black dye and nickel acetate

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

T252-d