Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-200-8471

| Thread Class:                         |  |
|---------------------------------------|--|
| 2a                                    |  |
| Thread Direction:                     |  |
| Right-hand                            |  |
| Casehardening Indicator:              |  |
| Not casehardened                      |  |
| Chamfer Angle In Deg:                 |  |
| 30.0                                  |  |
| Chamfer Length:                       |  |
| 0.109 inches                          |  |
| Width:                                |  |
| 0.250 inches                          |  |
| Overall Length:                       |  |
| 0.688 inches                          |  |
| Thread Size:                          |  |
| 2-3/8 in12                            |  |
| Bore Diameter:                        |  |
| Between 1.812 inches and 1.817 inches |  |
| Depth:                                |  |
| 0.094 inches                          |  |
| Bore Shape:                           |  |
| Straight                              |  |
| Screw Thread Series Designator:       |  |
| 12n                                   |  |
| Drive Type:                           |  |
| Slotted face                          |  |
| Accommodation Type And Quantity:      |  |
| 2 slots                               |  |
| Angle Between Accommodations In Deg:  |  |
| 180.0                                 |  |
| Beveled Thread:                       |  |
| Not included                          |  |
| Bore Annular Internal Serration:      |  |
| Not included                          |  |
| Setscrew Locking Notch:               |  |
| Not included                          |  |
| Bore Edge Process:                    |  |
| Chamfered                             |  |
| Process End Location:                 |  |
| End opposite drive end                |  |
| Material:                             |  |
| Steel, mil-s-16788                    |  |
|                                       |  |

# NSN 5365-00-200-8471

Externally Threaded Ring - Page 2 of 2



#### Material:

Steel comp 1010 or steel comp 1020 or steel comp 1030 or steel comp 1040 or steel comp 1050 or steel comp 1060 or steel comp 1080 or steel comp 1095

# Shelf Life:

N/a

## Unit Of Measure:

---

### Demilitarization:

No

Fiig:

T252-d