## NSN 5365-00-210-0766

**Thread Class:** 

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-210-0766

3a
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.250 inches
Overall Length:
0.750 inches
Thread Size:
1-5/3 in16
Bore Diameter:
1.250 inches
Depth:
0.125 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Ns
Drive Type:
Slotted face
Accommodation Type And Quantity:
4 slots
Angle Between Accommodations In Deg:
90.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
Unthreaded portion of ring machined to 1.560 in. Od., 1/4 in. Wide
Material:
Steel, qq-s-633, fs1040 to fs 1045 or fsc1137, sae, c1144
Material:
Steel, qq-s-633, fs1040 to fs 1045 or fsc1137, sae, c1144
Surface Treatment:
Phosphate zinc
Surface Treatment:
Phosphate, mil-c-16232, type 2-canceled

## NSN 5365-00-210-0766

Externally Threaded Ring - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d