

View Online at <https://aerobasegroup.com/nsn/5365-00-220-2050>

Thread Class:

2a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Width:

Between 0.031 inches and 0.062 inches

Overall Length:

Between 0.109 inches and 0.141 inches

Thread Size:

0.865 in.-32

Bore Diameter:

Between 0.730 inches and 0.740 inches

Depth:

Between 0.031 inches and 0.062 inches

Unit Package Type:

Envelope, heat sealed

Bore Shape:

Straight

Screw Thread Series Designator:

Nonstandard

Drive Type:

Slotted face

Thread Location:

End opposite drive end

Accommodation Type And Quantity:

2 slots

Angle Between Accommodations In Deg:

180.0

Beveled Thread:

Included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Material:

Aluminum alloy, ww-t-700/3, alloy 2024, temper t3 or t42

Material:

Aluminum alloy, ww-t-700/3, alloy 2024, temper t3 or t42

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1, class 2, black military specification single treatment response

Surface Treatment:

Anodized, mil-a-8625, type 1, class 2, black

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-d

Mil-std (military Standard):

Mil-a-8625 spec.