## NSN 5365-00-241-0083

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-241-0083

Thread Pitch Diameters:
+3.1640 to 3.1686 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Chamfer Angle In Deg:
50.0
Chamfer Length:
0.040 inches
Width:
Between 0.235 inches and 0.245 inches
Overall Length:
Between 0.585 inches and 0.595 inches
Thread Size:
3.190 in32
Bore Diameter:
Between 2.938 inches and 2.940 inches
Depth:
0.280 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Ns
Drive Type:
Slotted face
Material Hardness Rating:
Between 29.0 rockwell c and 38.0 rockwell c
Thread Location:
Both ends
Accommodation Type And Quantity:
10 slots
Angle Between Accommodations In Deg:
36.0
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
Chamfered

## NSN 5365-00-241-0083

Externally Threaded Ring - Page 2 of 2



Pro	ce	SS	End	1	l o	ca	ti	OΙ	n:

End opposite drive end

Material:

Steel, corrosion resisting

Material:

Stainless steel

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

T252-d