NSN 5365-00-241-0083

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-241-0083

| Thread Pitch Diameters: |
|---|
| +3.1640 to 3.1686 inches |
| Thread Direction: |
| Right-hand |
| Casehardening Indicator: |
| Not casehardened |
| Chamfer Angle In Deg: |
| 50.0 |
| Chamfer Length: |
| 0.040 inches |
| Width: |
| Between 0.235 inches and 0.245 inches |
| Overall Length: |
| Between 0.585 inches and 0.595 inches |
| Thread Size: |
| 3.190 in32 |
| Bore Diameter: |
| Between 2.938 inches and 2.940 inches |
| Depth: |
| 0.280 inches |
| Bore Shape: |
| Straight |
| Screw Thread Series Designator: |
| Ns |
| Drive Type: |
| Slotted face |
| Material Hardness Rating: |
| Between 29.0 rockwell c and 38.0 rockwell c |
| Thread Location: |
| Both ends |
| Accommodation Type And Quantity: |
| 10 slots |
| Angle Between Accommodations In Deg: |
| 36.0 |
| Beveled Thread: |
| Included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Bore Edge Process: |
| Chamfered |
| |

NSN 5365-00-241-0083

Externally Threaded Ring - Page 2 of 2



| Pro | ce | SS | End | 1 | l o | ca | ti | OΙ | n: |
|-----|----|----|-----|---|-----|----|----|----|----|
| | | | | | | | | | |

End opposite drive end

Material:

Steel, corrosion resisting

Material:

Stainless steel

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

T252-d