

View Online at <https://aerobasegroup.com/nsn/5365-00-259-2252>

**Thread Direction:**

Right-hand

**Countersink Angle In Deg:**

40.0

**Counterbore Diameter:**

Between 1.080 inches and 1.090 inches

**Counterbore Depth:**

Between 0.280 inches and 0.285 inches

**Overall Length:**

Between 0.666 inches and 0.676 inches

**Thickness:**

Between 0.246 inches and 0.256 inches

**Wrenching Facility Shape:**

Hexagon

**Countersink Depth:**

0.040 inches

**Screw Thread Length:**

0.420 inches

**Width Across Flats:**

1.125 inches

**Counterbore Location:**

Threaded end

**Countersink Location:**

Threaded end

**Hole Inside Diameter:**

Between 0.760 inches and 0.770 inches

**Features Provided:**

Counterbore and countersunk

**Thready Qty Per Inch (tpi):**

12

**Thread Size:**

1.375 inches

**Special Features:**

2 0.040 in. Min 0.050 in. Maximum holes drilled through opposite corners, second countersunk angle: 50.0 deg

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-225/8, t651 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Ps13201, type 2, class 1, 76301 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A540s0