## NSN 5365-00-259-2252

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-259-2252

Thread Direction:
Right-hand
Countersink Angle In Deg:
40.0
Counterbore Diameter:
Between 1.080 inches and 1.090 inches
Counterbore Depth:
Between 0.280 inches and 0.285 inches
Overall Length:
Between 0.666 inches and 0.676 inches
Thickness:
Between 0.246 inches and 0.256 inches
Wrenching Facility Shape:
Hexagon
Countersink Depth:
0.040 inches
Screw Thread Length:
0.420 inches
Width Across Flats:
1.125 inches
Counterbore Location:
Threaded end
Countersink Location:
Threaded end
Hole Inside Diameter:
Between 0.760 inches and 0.770 inches
Features Provided:
Counterbore and countersunk
Thready Qty Per Inch (tpi):
12
Thread Size:
1.375 inches
Special Features:
2 0.040 in.Min 0.050 in. Maximum holes drilled through opposite corners, second countersunk angle: 50.0 deg
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-225/8, t651 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:

Ps13201, type 2, class 1, 76301 mfr ref single treatment response

## NSN 5365-00-259-2252

Machine Thread Bushing - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig:

A540s0