

View Online at <https://aerobasegroup.com/nsn/5365-00-261-2882>

Thread Class:

2a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Width:

Between 0.235 inches and 0.245 inches

Overall Length:

Between 0.625 inches and 0.650 inches

Thread Size:

3.190-32

Depth:

Between 0.080 inches and 0.100 inches

Screw Thread Series Designator:

Uns

Drive Type:

Slotted face

Material Hardness Rating:

Between 28.0 rockwell c and 39.0 rockwell c

Accommodation Type And Quantity:

10 slots

Angle Between Accommodations In Deg:

36.0

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Material:

Steel ams 5737 or steel b50t1181a2 99207

Material:

Steel ams 5737 or steel b50t1181a2 99207

Test Data Document:

99207-a+3tf 2, cl a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-d