

View Online at <https://aerobasegroup.com/nsn/5365-00-261-2882>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

Between 0.235 inches and 0.245 inches

**Overall Length:**

Between 0.625 inches and 0.650 inches

**Thread Size:**

3.190-32

**Depth:**

Between 0.080 inches and 0.100 inches

**Screw Thread Series Designator:**

Uns

**Drive Type:**

Slotted face

**Material Hardness Rating:**

Between 28.0 rockwell c and 39.0 rockwell c

**Accommodation Type And Quantity:**

10 slots

**Angle Between Accommodations In Deg:**

36.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Material:**

Steel ams 5737 or steel b50t1181a2 99207

**Material:**

Steel ams 5737 or steel b50t1181a2 99207

**Test Data Document:**

99207-a+3tf 2, cl a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d