NSN 5365-00-275-6030

Thread Class:

Right-hand

Width:

Depth:

0.062 inches

Bore Shape:

0.062 inches

Overall Length:
0.406 inches

Thread Size:
2.9375 in. -32

Bore Diameter:
2.687 inches

Thread Direction:

Not casehardened

Casehardening Indicator:

2a

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-275-6030

Straight
Screw Thread Series Designator:
Ns
Drive Type:
Slotted face
Thread Location:
End opposite drive end
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Brass, qq-b-626
Material:
Copper alloy 268 or copper alloy 260 or copper alloy 240 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 342 or
copper alloy 353 or copper alloy 262 or copper alloy 270 or copper alloy 272 or copper alloy 274 or copper alloy 280 or copper alloy 330 or
copper alloy 331 or copper alloy 332 or copper alloy 335 or copper alloy 340 or copper alloy 344 or copper alloy 345 or copper alloy 347 or
copper alloy 348 or copper alloy 350 or copper alloy 356 or copper alloy 370 or copper alloy 462 or copper alloy 464 or copper alloy 465 or
copper alloy 466 or copper alloy 467 or copper alloy 482 or copper alloy 485
Surface Treatment:
Oxide
Surface Treatment

NSN 5365-00-275-6030

Externally Threaded Ring - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d