# NSN 5365-00-275-6040

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-275-6040 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.031 inches Width: 0.250 inches **Overall Length:** 0.563 inches **End Radius:** 0.125 inches **Thread Size:** 1.967 in. -18 **Bore Diameter:** 1.313 inches Depth: 0.188 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Ns **Drive Type:** Slotted face **Thread Location:** Drive end **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 60.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included

**Bore Edge Process:** 

Chamfered

# NSN 5365-00-275-6040

Externally Threaded Ring - Page 2 of 2



_				_					
	rn	$\sim$	66	-n	<b>'</b>		oca	t1/	۱n:
	··	CE	33		u	_	Jua	u	,,,,

End opposite drive end

## **Special Features:**

End opposite to drive end relieved 27/32 in. Porm 1/64 diameter by 1/16 in. Porm 1/64 lg

### Material:

Steel, qq-s-634-canceled

### Material:

Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050

### Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### **Demilitarization:**

No

### Fiig:

T252-d