NSN 5365-00-275-6047

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-275-6047 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.075 inches and 0.087 inches **Overall Length:** Between 0.198 inches and 0.208 inches **Thread Size:** 13/16 in. -20 **Bore Diameter:** Between 0.564 inches and 0.566 inches Between 0.053 inches and 0.073 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Nef **Drive Type:** Slotted face **Thread Location:** Both ends **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** End opposite to drive end counterbored 0.627 to 0.629 in. Diameter by 0.080 to 0.090 in. Deep Material: Brass, mil-b-994, comp b, 1/2 hard-canceled Material: Copper alloy 482 Shelf Life:

N/a

NSN 5365-00-275-6047

Externally Threaded Ring - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

T252-d