

View Online at <https://aerobasegroup.com/nsn/5365-00-277-7565>

Thread Direction:

Right-hand

Countersink Angle In Deg:

45.0

Overall Length:

Between 1.000 inches and 1.004 inches

Diameter:

Between 1.097 inches and 1.100 inches

Thickness:

Between 0.447 inches and 0.490 inches

Wrenching Facility Shape:

Round

Countersink Depth:

0.093 inches

Screw Thread Length:

0.750 inches

Countersink Location:

Threaded end

Hole Inside Diameter:

Between 0.447 inches and 0.449 inches

Features Provided:

Countersunk

Thready Qty Per Inch (tpi):

14

Thread Size:

0.875 inches

Special Features:

Two 0.128 in. Diameter holes spaced 180 degrees apart 0.125 in. Deep in face of rd part on 0.748 in. Min 0.752 in. Maximum diameter bolt circle, thd undercut to 0.740 in. Min 0.760 in. Maximum diameter adjacent to hex 0.146 in. Min 0.166 in. Max, thd undercut to 0.740 in. Min 0.750 in. Maximum diameter on end 0.115 in min 0.135 in. Maximum lg

Material:

Steel

Thread Series Designator:

Unf

Fsc Application Data:

Projector dept charge

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A540s0