

View Online at <https://aerobasegroup.com/nsn/5365-00-277-7565>

**Thread Direction:**

Right-hand

**Countersink Angle In Deg:**

45.0

**Overall Length:**

Between 1.000 inches and 1.004 inches

**Diameter:**

Between 1.097 inches and 1.100 inches

**Thickness:**

Between 0.447 inches and 0.490 inches

**Wrenching Facility Shape:**

Round

**Countersink Depth:**

0.093 inches

**Screw Thread Length:**

0.750 inches

**Countersink Location:**

Threaded end

**Hole Inside Diameter:**

Between 0.447 inches and 0.449 inches

**Features Provided:**

Countersunk

**Thready Qty Per Inch (tpi):**

14

**Thread Size:**

0.875 inches

**Special Features:**

Two 0.128 in. Diameter holes spaced 180 degrees apart 0.125 in. Deep in face of rd part on 0.748 in. Min 0.752 in. Maximum diameter bolt circle, thd undercut to 0.740 in. Min 0.760 in. Maximum diameter adjacent to hex 0.146 in. Min 0.166 in. Max, thd undercut to 0.740 in. Min 0.750 in. Maximum diameter on end 0.115 in min 0.135 in. Maximum lg

**Material:**

Steel

**Thread Series Designator:**

Unf

**Fsc Application Data:**

Projector dept charge

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A540s0