
Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-285-7932

| 3a | ead Class: |
|-------|------------------------------------|
| | |
| | ead Direction: |
| - | |
| | ehardening Indicator: |
| | casehardened |
| Wid | |
| | 33 inches |
| | erall Length: |
| | 20 inches |
| | ead Size: |
| | 5/32 in32 |
| | e Diameter: |
| | 50 inches |
| Dep | oth: |
| 0.05 | 50 inches |
| Bor | e Shape: |
| Stra | light |
| Scre | ew Thread Series Designator: |
| Uns | |
| Driv | /е Туре: |
| Slot | ted face |
| Acc | commodation Type And Quantity: |
| 2 slo | ots |
| Ang | le Between Accommodations In Deg: |
| 180. | .0 |
| Bev | reled Thread: |
| Not | included |
| Bor | e Annular Internal Serration: |
| Inclu | uded |
| Sets | screw Locking Notch: |
| Not | included |
| Mat | erial: |
| Alur | ninum alloy, ww-t-785, t3-canceled |
| Mat | erial: |
| Alur | ninum alloy 2024 |
| Sur | face Treatment: |
| Blac | ck dye |
| She | If Life: |
| N/a | |
| | t Of Measure: |

NSN 5365-00-285-7932

Externally Threaded Ring - Page 2 of 2

AeroBase Group

Demilitarization:

No

Fiig:

T252-d