

View Online at <https://aerobasegroup.com/nsn/5365-00-290-0933>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Overall Length:**

0.313 inches

**Diameter:**

0.188 inches

**Thread Size:**

1-3/8 in. -16 thd size

**Bore Diameter:**

0.625 inches

**Depth:**

0.125 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

16n

**Drive Type:**

Drilled face

**Accommodation Type And Quantity:**

4 holes

**Angle Between Accommodations In Deg:**

90.0

**Radius From Geometric Axis To Accommodation:**

0.516 inches

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

End opposite drilled face reduced to 1-9/32 in. Diameter by 3/32 in. Porm 1/64 long and counter bored to 1-1/16 in. Diameter by 3/32 in. Porm 1/64 in. Deep and end opposite drilled face slotted 1/8 in. Wide by 3/32 in. Porm 1/64 deep 90 degrees apart

**Material:**

Steel, n, 46-s-17, class 1 or steel, n, 46-s-17, class 2

**Material:**

Steel comp 1115 or steel comp 1117 or steel comp 1120 or steel comp 1211 or steel comp 1212

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d