NSN 5365-00-291-3531

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-291-3531 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.031 inches Width: 0.063 inches **Overall Length:** 0.188 inches **Thread Size:** 1/2 in. -20 **Bore Diameter:** 0.257 inches Depth: 0.063 inches Bore Shape: Straight **Screw Thread Series Designator:** Unf **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** Both ends

Unif
Drive Type:
Slotted face
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations in Deg:
180.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
Chamfered
Process End Location:
Both ends
Material:
Steel, qq-s-634, comp 1020-canceled

NSN 5365-00-291-3531

Externally Threaded Ring - Page 2 of 2



M	lat	Or	וכו	

Steel comp 1020

Surface Treatment:

Oxide

Surface Treatment:

Black oxide

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d