NSN 5365-00-291-3579

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-291-3579 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.168 inches Diameter: 0.059 inches **Thread Size:** 1.202 in. -40 **Bore Diameter:** 0.8599 inches Depth: 0.153 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Ns **Drive Type:** Drilled face **Accommodation Type And Quantity:** 2 holes Angle Between Accommodations In Deg: 180.0 **Radius From Geometric Axis To Accommodation:** 0.516 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Counterbore 1.031 in. Plus 0.010 diameter 0.015 in. Deep and 0.073 in.-72 nf 3 tapped hole on 0.531 in. Radius midway between other two holes and internally threaded with 0.089 in.-36 uns-3 thread size Material: Brass Material:

Oxide

Copper alloy

Surface Treatment:

NSN 5365-00-291-3579

Externally Threaded Ring - Page 2 of 2



| _ | • | | _ | | | | |
|----------|------|--------|-----|---|----|----|--|
| <u>ن</u> | urfa | \sim | l r | 2 | ŀm | Δn | |
| | | | | | | | |

Black oxide

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d