## NSN 5365-00-292-3198

Aluminum alloy 2024

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-292-3198

Thread Pitch Diameters:
+2.0735 to 2.0783 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.625 inches
Overall Length:
Between 0.169 inches and 0.170 inches
Taper Minor Diameter:
1.844 inches
Taper Major Diameter:
1.940 inches
Thread Size:
2.094-32
Depth:
0.060 inches
Bore Shape:
Tapered
Screw Thread Series Designator:
Ns
Drive Type:
Slotted face
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Not included
Taper Major Diameter Location:
Opposite drive end
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
Counterbored 1/32 in. Deep, 5 degrees plus or minus 30 min angle of chamfer 2-1/32 in. Diameter internally end opposite to drive end
Material:
Aluminum alloy, ww-t-785, t3-canceled
Material:

## NSN 5365-00-292-3198

Fiig: T252-d

Externally Threaded Ring - Page 2 of 2



Surface Treatment:
Anodize or anodize
Surface Treatment:
Anodized, mil-a-8625, type 1, class 2 or anodized, mil-a-8625, type 2, class 2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No