## NSN 5365-00-302-9123

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-302-9123 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 43.0 and 47.0 **Chamfer Length:** 0.060 inches Width: 0.320 inches **Overall Length:** 1.190 inches **Thread Size:** 4.500-12 **Bore Diameter: 3.737** inches Depth: 0.425 inches Bore Shape: Straight **Screw Thread Series Designator:** Unj **Drive Type:** Externally slotted **Accommodation Type And Quantity:** 8 slots Angle Between Accommodations In Deg: 43.0 and 47.0 **Beveled Thread:** 

Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** Both ends Material: Aluminum alloy qq-a-225/9 alloy 7075 temper t6

## NSN 5365-00-302-9123

Externally Threaded Ring - Page 2 of 2



RЛ	ate	ria	ι.
IVI	ale	па	Ι.

Aluminum alloy qq-a-225/9 alloy 7075 temper t6

## **Surface Treatment:**

Anodize lcp77-2037 class 1 grade a type 1 fscm 36659

## **Surface Treatment:**

Anodize lcp77-2037 class 1 grade a type 1 fscm 36659

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

T252-d