

View Online at <https://aerobasegroup.com/nsn/5365-00-302-9123>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

43.0 and 47.0

**Chamfer Length:**

0.060 inches

**Width:**

0.320 inches

**Overall Length:**

1.190 inches

**Thread Size:**

4.500-12

**Bore Diameter:**

3.737 inches

**Depth:**

0.425 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unj

**Drive Type:**

Externally slotted

**Accommodation Type And Quantity:**

8 slots

**Angle Between Accommodations In Deg:**

43.0 and 47.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Both ends

**Material:**

Aluminum alloy qq-a-225/9 alloy 7075 temper t6

**Material:**

Aluminum alloy qq-a-225/9 alloy 7075 temper t6

**Surface Treatment:**

Anodize lcp77-2037 class 1 grade a type 1 fscm 36659

**Surface Treatment:**

Anodize lcp77-2037 class 1 grade a type 1 fscm 36659

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d