

View Online at <https://aerobasegroup.com/nsn/5365-00-302-9135>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

0.200 inches

**Overall Length:**

1.340 inches

**Thread Size:**

2.750-12

**Bore Diameter:**

2.000 inches

**Depth:**

0.380 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unj

**Drive Type:**

Slotted face

**Thread Location:**

Drive end

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

Counterbored from drive end 2.290 in. Diameter 1.200 in. Deep, four holes drilled through unthreaded portion of ring in. Max diameter spaced 45 degrees from slot centers

**Material:**

Steel mil-s-5000 composition e4340 physical condition e surface condition 1

**Material:**

Steel mil-s-5000 composition e4340 physical condition e surface condition 1

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Lc+77-1061 36659 mfr ref single treatment response

**Surface Treatment:**

Cadmium plate lcp77-1061 36659

**Test Data Document:**

36659-lc+72-1076 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d