Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-308-5475

View Online at https://aerobasegroup.com/nsn/5365-00-308-5475
Thread Class:
3a
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.062 inches
Overall Length:
0.312 inches
Thread Size:
2.375 in 32
Bore Diameter:
2.000 inches
Depth:
0.062 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Slotted face
Thread Location:
End opposite drive end
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Special Features:
1/32 in. Wide slot cut horizontal to threads 3/32 in. From drive end of ring to within 25/32 in. Of longitudinal axis
Material:
Aluminum alloy, qq-a-268, cond t4-canceled
Material:
Aluminum alloy 2024
Surface Treatment:
Anodize

NSN 5365-00-308-5475

Externally Threaded Ring - Page 2 of 2



Surface Treatment:

Anodized

Fsc Application Data:

Antenna, tracking, fire control radar equipment, except airborne

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d