NSN 5365-00-310-9278

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-310-9278 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Chamfer Angle In Deg: 45.0 **Chamfer Length:** Between 0.020 inches and 0.040 inches Width: Between 0.140 inches and 0.160 inches **Overall Length:** Between 0.420 inches and 0.440 inches **Thread Size:** 7/8 /0.875/ in. -14 **Bore Diameter:** Between 0.610 inches and 0.620 inches Depth: Between 0.100 inches and 0.120 inches Bore Shape: Straight **Screw Thread Series Designator:** Unf or nf **Drive Type:** Slotted face **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:**

End opposite drive end

NSN 5365-00-310-9278

Externally Threaded Ring - Page 2 of 2



М	ate	ria	۱.
IVI	ale	па	ı .

Steel, ams 5022

Material:

Steel comp 1117

Surface Treatment:

Cadmium

Surface Treatment:

Cadmium plated

Fsc Application Data:

Engine, turbojet

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

T252-d