## NSN 5365-00-311-8280

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-311-8280 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.210 inches **Overall Length:** 1.140 inches **Thread Size:** 2.250-12 **Bore Diameter:** 1.078 inches Depth: 0.360 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Counterbore from drive end 1.860 in. Diameter 1.030 in. Depth Material: Steel mil-s-5000 composition e4340 physical condition e surface condition 1 Material: Steel mil-s-5000 composition e4340 physical condition e surface condition 1 **Surface Treatment:** 

ourrace rreatime

Cadmium

## NSN 5365-00-311-8280

Externally Threaded Ring - Page 2 of 2



## **Surface Treatment Specification:**

Lc+77-1061 36659 mfr ref single treatment response

**Surface Treatment:** 

Cadmium plate lcp77-1061 36659

## **Test Data Document:**

36659-lc+72-1076 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Sh	۵lf	Life:
911	CII	LIIE.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d