## NSN 5365-00-312-1039

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-312-1039 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.250 inches **Overall Length:** 0.750 inches **Thread Size:** 1.250-12 **Bore Diameter:** Between 0.975 inches and 0.985 inches Depth: 0.125 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unjf **Drive Type:** Slotted face **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Material: Aluminum alloy qq-a-220/11 alloy 7075 temper t73511 or aluminum alloy qq-a-225/9 alloy7075 temper t7351 Material: Aluminum alloy qq-a-200/11 alloy 7075 temper t73511 or aluminum alloy qq-a-225/9 alloy7075 temper t7351 **Surface Treatment:** Anodize **Surface Treatment Specification:** 

Surface Treatment:

Anodized mil-a-8625 type 2

Mil-a-8625 type 2 military specification single treatment response

## NSN 5365-00-312-1039

Externally Threaded Ring - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
T252-d	

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: