

View Online at <https://aerobasegroup.com/nsn/5365-00-316-5588>

Thread Class:

3a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Chamfer Angle In Deg:

45.0

Chamfer Length:

Between 0.015 inches and 0.020 inches

Width:

0.062 inches

Overall Length:

0.139 inches

Thread Size:

0.750-32

Bore Diameter:

0.540 inches

Depth:

0.050 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Un

Drive Type:

Slotted face

Thread Location:

End opposite drive end

Accommodation Type And Quantity:

2 slots

Angle Between Accommodations In Deg:

180.0

Beveled Thread:

Included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Bore Edge Process:

Chamfered

Process End Location:

End opposite drive end

Special Features:

Diamond knurl on id

Material:

Aluminum alloy qq-a-225/6 alloy 2024 temper t4 or temper t351 or aluminum alloy qq-a-200/3 alloy 2024 temper t4

Material:

Aluminum alloy qq-a-225/6 alloy 2024 temper t4 or temper t351 or aluminum alloy qq-a-200/3 alloy 2024 temper t4

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 type 2 class 2 military specification single treatment response

Surface Treatment:

Anodize mil-a-8625 type 2 class 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d

Mil-std (military Standard):

Mil-a-8625 spec.