## NSN 5365-00-317-4765

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-317-4765 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.250 inches and 0.260 inches **Overall Length:** 0.630 inches **Thread Size:** 3.000-12 **Bore Diameter:** 2.500 inches Depth: 0.290 inches Bore Shape: Straight **Screw Thread Series Designator:** Unj **Drive Type:** Slotted face **Thread Location:** Both ends **Accommodation Type And Quantity:** 4 slots Angle Between Accommodations In Deg: 90.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Two 0.050 in. Diameter holes 180 degrees apart drilled at 45 degrees angle on face to ring id centered between drive slots Material: Steel ams 5643 or steel ams 5658 or steel ams 5659

Material:

Steel ams 5643 or steel ams 5658 or steel ams 5659

**Surface Treatment:** 

Passivated ps13001 76301

## NSN 5365-00-317-4765

Externally Threaded Ring - Page 2 of 2



$\overline{}$			-			
<u>ن</u>	irto	2	Iro	atn	าคท	

Passivated ps13001 76301

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d