NSN 5365-00-321-4791

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-321-4791

View Online at https://aerobasegroup.com/nsn/5365-00-321-4791
Thread Direction:
Right-hand
Countersink Angle In Deg:
90.0 wrenching end, first countersink
Counterbore Diameter:
0.625 inches and 0.630 inches wrenching end, first counterbore
Counterbore Depth:
0.290 inches wrenching end, first counterbore
Overall Length:
Between 0.710 inches and 0.730 inches
Thickness:
Between 0.330 inches and 0.350 inches
Wrenching Facility Shape:
Hexagon
Countersink Depth:
0.096 inches wrenching end, first countersink
End Application:
Landing gear specific
Screw Thread Length:
0.309 inches
Width Across Flats:
1.000 inches
Counterbore Location:
Wrenching end
Countersink Location:
Wrenching end
Hole Inside Diameter:
Between 0.3765 inches and 0.3785 inches
Features Provided:
Counterbore and countersunk
Thready Qty Per Inch (tpi):
14
Thread Size:
0.875 inches
Criticality Code Justification:
Agav
Special Features:
Has three holes equally spaced through sides of wrenching facility w/dia. Of 0.069 in. Min. And 0.074 in. Max.
Material:
Aluminum alloy 2024
Material Specification:

Qq-a-225/6, t351 federal specification single material response

NSN 5365-00-321-4791

Machine Thread Bushing - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: No

Fiig:

A540s0